

Also available in type K, T or L* and classes 1 or 2!

For the temperature collection at conduits, generally spoken at all cylindric dimensions as well as at plastics processing machines. Fixing by pipe clamp. The stainless steel wire armouring of the connection cable is used as mechanical protection.

THERMOCOUPLE - CLASS 2:

- 1 x type J 1 x type K
- other thermocouples: _____

MEASURING POINT:

- form B, grounded measuring point

MATERIAL:

- 1.4571

NOMINAL LENGTH:

- 38 mm
- _____ mm

DIAMETER:

- Ø 6,0 mm

FIX ACCESSORIES:

- sheet 15 x 30 mm, radius: 28 mm
- _____



TEMPERATURE RANGE:

- + 400°C

CONNECTION CABLE:

(see also survey of connecting cables for thermocouples)

- extension cable strand/fiber glass/fiber glass/
stainless steel wire armouring +400°C
- extension cable strand/PFA/fiber glass/
stainless steel wire armouring +250°C
- _____

CABLE LENGTH: _____ m

CONNECTION ENDS:

- miniature thermoplug miniature socket
- standard plug Lemo plug type _____
- clips Lemo socket type _____
- bare ends other cable ends _____



- The above mentioned technical data are standard data.
- Individual parameters, e. g. connection cable, double thermocouple, radius or cable end can be added or modified on request.