

## SABIX® A 812 C FRNC Motor connection cable with numbered cores, improved fire performance, inner sheath, overall copper screen and extended temperature range

D-VIERSEN · SABIX A 812 C FRNC rf 0,6/1 kV 7 x 1,5 mm<sup>2</sup> CE



Marking for SABIX A 812 C FRNC 68120715:  
SAB BRÖCKSKES · D-VIERSEN · SABIX A 812 C FRNC rf 0,6/1 kV 7 x 1,5 mm<sup>2</sup> CE

A  
34

### Construction:

<b>Conductor:</b>	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
<b>Insulation:</b>	SABIX®
<b>Colour code:</b>	black cores with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 cores
<b>Stranding:</b>	in layers
<b>Inner sheath:</b>	SABIX®
<b>Screen:</b>	tinned copper braiding
<b>Sheath material:</b>	SABIX®
<b>Sheath colour:</b>	grey (RAL 7000)

### Outstanding features:

- halogen-free
- good EMC characteristics\*
- no flame propagation
- flame retardant and self-extinguishing
- EAC approval

\* Copper braiding should be connected circularly to optimize the EMC characteristics

### Technical data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 0.6/1 kV
<b>Testing voltage U:</b>	4000 V acc. to DIN VDE 0281 part 2 + HD 21.2 core/screen 2000 V
<b>Min. bending radius</b>	
<i>fixed laying:</i>	5 x d
<i>flexible application:</i>	10 x d
<b>Temperature range</b>	
<i>fixed laying:</i>	-40/+85 °C
<i>flexible application:</i>	-30/+85 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 + IEC 60754-1
<b>Fire performance:</b>	no flame propagation acc. to IEC 60332 + EN 60332 cat. C resp. D (see page N/19). Flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
<b>Corrosiveness of conflagration gases:</b>	in compliance with IEC 60754-2 + EN 50267-2-2 + VDE 0482 part 267-2-2 - no development of corrosive conflagration gases
<b>Smoke density:</b>	acc. to IEC 61034 + EN 61034
<b>Flexibility:</b>	good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
68120315	3 x 1,50	0,26	11,3	90,9	202
68120415	4 x 1,50	0,26	12,0	111,7	226
68120715	7 x 1,50	0,26	13,8	160,8	312
68120325	3 x 2,50	0,26	12,6	126,5	258
68120425	4 x 2,50	0,26	13,5	155,8	298
68120525	5 x 2,50	0,26	15,0	216,9	373
68120725	7 x 2,50	0,26	16,2	266,9	437
68120440	4 x 4,00	0,31	16,3	251,6	454
68120740	7 x 4,00	0,31	18,0	379,9	589
68120360	3 x 6,00	0,31	15,1	270,0	426
68120460	4 x 6,00	0,31	16,7	328,8	516
68120760	7 x 6,00	0,31	19,9	528,3	777

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
68120370	3 x 10,0	0,41	19,4	412,3	614
68120470	4 x 10,0	0,41	21,0	522,4	746
68120570	5 x 10,0	0,41	22,8	645,5	916
68120770	7 x 10,0	0,41	25,1	842,0	1154
68120380	3 x 16,0	0,41	22,4	601,9	827
68120480	4 x 16,0	0,41	24,7	783,4	1055
68120580	5 x 16,0	0,41	27,0	942,8	1291
68120780	7 x 16,0	0,41	29,7	1274,0	1661
68120390	3 x 25,0	0,41	26,7	894,0	1188
68120490	4 x 25,0	0,41	29,4	1157,7	1510
68120590	5 x 25,0	0,41	32,3	1413,6	1862

Other dimensions and colours are possible on request.