

# HALOGEN-FREE CABLES

## SABIX® BL 415 C FRNC halogen-free flexible data cable with overall copper screen

BL = BlueLine



Marking for SABIX BL 415 C FRNC 64150750: SAB BRÖCKSKES · D-VIERSEN · SABIX BL 415 C FRNC 7x0,5mm<sup>2</sup> - IEC 60332-3-22 - 350V DNV-GL ABS Assessed Lloyd's Register CE and current meter marking

A  
63

### Construction:

<b>Conductor:</b>	tinned copper strands acc. to DIN VDE 0812 resp. IEC 60228, EN 60228, VDE 0295, class 5
<b>Insulation:</b>	special SABIX®
<b>Colour code:</b>	with reference to DIN 47100
<b>Stranding:</b>	in layers
<b>Wrapping:</b>	PETP foil
<b>Screen:</b>	tinned copper braiding
<b>Sheath material:</b>	special SABIX® SHF 1 compound acc. to IEC 60092-359
<b>Sheath colour:</b>	pigeon blue (RAL 5014)

### Outstanding features:

- halogen-free
- asbestos-free
- good EMC characteristics\*
- no flame propagation
- flame retardant and self-extinguishing
- flexible
- for applications acc. to Hong Kong Convention ingredients tested acc. to the requirements of the Hong Kong Convention (2009) of the IMO
- approvals:  
Det Norske Veritas - Germanischer Lloyd  
Lloyd's Register  
American Bureau of Shipping  
Registro Italiano Navale
- EAC approval

\* Copper braiding should be connected circularly to optimize the EMC characteristics

### Technical data:

<b>Peak operating voltage:</b>	max. 350 V
<b>Testing voltage:</b>	core/core 1500 V core/screen 1200 V
<b>Min. bending radius</b>	
fixed laying:	5 x d
flexible application:	10 x d
<b>Temperature range</b>	
fixed laying:	-40/+90 °C
flexible application:	-30/+90 °C
<b>Halogen-free:</b>	acc. to EN 50267-2-1 + IEC 60754-1
<b>Fire performance:</b>	no flame propagation acc. to IEC 60332-3-22 + DIN EN 60332-3-22 cat. A. Flame retardant and self-extinguishing acc. to IEC 60332-1-2 + DIN EN 60332-1-2
<b>Corrosiveness of conflagration gases:</b>	in compliance with IEC 60754-2 + DIN EN 50267-2-2 - no development of corrosive conflagration gases
<b>Smoke density:</b>	acc. to IEC 61034 + EN 61034
<b>Flexibility:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

### Possible on request:



- bare copper strands
- alternative colour code and sheath colour

item no.	no. of cores x cross section n x mm <sup>2</sup>	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
64150214	2 x 0,14	4,1	13,0	25
64150314	3 x 0,14	4,3	14,4	29
64150414	4 x 0,14	4,6	19,3	35
64150514	5 x 0,14	5,0	20,7	40
64150614	6 x 0,14	5,3	22,2	43
64150714	7 x 0,14	5,3	23,5	45
64150814	8 x 0,14	6,2	28,4	57
64151214	12 x 0,14	6,8	35,8	70
64151614	16 x 0,14	7,5	43,0	85
64150225	2 x 0,25	4,4	18,6	32
64150325	3 x 0,25	4,6	21,1	36
64150425	4 x 0,25	5,0	23,6	41
64150525	5 x 0,25	5,4	27,9	49
64150625	6 x 0,25	5,8	30,5	54
64150725	7 x 0,25	5,8	32,9	57
64150825	8 x 0,25	6,7	38,8	71
64151225	12 x 0,25	7,5	50,3	89
64151625	16 x 0,25	8,6	62,2	118

item no.	no. of cores x cross section n x mm <sup>2</sup>	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
64150234	2 x 0,34	4,8	20,5	37
64150334	3 x 0,34	5,1	23,8	42
64150434	4 x 0,34	5,5	29,0	50
64150534	5 x 0,34	6,1	32,4	61
64150634	6 x 0,34	6,6	39,1	71
64150734	7 x 0,34	6,6	42,4	75
64150834	8 x 0,34	7,5	47,6	88
64151234	12 x 0,34	8,7	65,3	121
64151634	16 x 0,34	9,5	81,2	149
64150250	2 x 0,50	5,2	23,7	43
64150350	3 x 0,50	5,5	30,3	52
64150450	4 x 0,50	6,1	35,3	64
64150550	5 x 0,50	6,6	43,5	77
64150650	6 x 0,50	7,2	50,1	85
64150750	7 x 0,50	7,2	54,9	90
64150850	8 x 0,50	8,6	62,2	116
64151250	12 x 0,50	9,5	86,6	152
64151650	16 x 0,50	10,7	124,5	201
64150275	2 x 0,75	5,7	30,4	52
64150375	3 x 0,75	6,2	39,2	65
64150475	4 x 0,75	6,7	48,4	78
64150575	5 x 0,75	7,3	57,4	93
64150675	6 x 0,75	7,9	66,9	106
64150775	7 x 0,75	7,9	74,1	114
64150875	8 x 0,75	9,3	83,9	142
64151275	12 x 0,75	10,8	134,2	194
64151675	16 x 0,75	11,8	169,6	247

Other dimensions and colours are possible on request.



Especially for use  
in shipbuilding industry