



SL 863 C Low capacity combined PVC motor connection cable with overall copper screen 0,6/1 kV

0 mm² + (2 x 1,50 mm²) AWM Style 21179 80°C 1000V CE



Marking for SL 863 C 08631415:

SAB BRÖCKSKES · D-VIERSEN · 08631415 4 x 1,50 mm² + (2 x 1,50 mm²) AWM Style 21179 80°C 1000V CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
Insulation:	special Polymer
Colour code:	black cores with consecutive numbers acc. to EN 50334 and a green-yellow earth wire supply cores: U1, V2, W3 and a green-yellow earth wire control cores: BR1 and BR2
Stranding:	control cores twisted to pair
Screen:	tinned copper braid
Wrapping:	PETP foil
Stranding:	screened control pair and supply cores twisted together in layer
Wrapping:	PETP foil
Screen:	tinned copper braid
Sheath material:	PVC
Sheath colour:	orange (RAL 2003)

Outstanding features:

- UL recognized
- very good EMC characteristics
- very good stripping
- low capacity construction
- very good oil resistance

Technical data:

Nominal voltage:	supply cores U ₀ /U 0.6/1 kV	
Voltage UL:	supply cores 1000 V	
Peak operating voltage:	control cores max. 350 V	
Voltage UL:	control cores 1000 V	
Testing voltage:	supply cores	core/core 4000 V core/screen 4000 V
	control cores	core/core 2000 V core/screen 2000 V
Min. bending radius		
<i>fixed laying:</i>	5 x d	
<i>flexible application:</i>	10 x d	
Temperature range	DIN VDE	UL: up to +80°C
<i>fixed laying:</i>	-30/+70 °C	
<i>flexible application:</i>	+0/+70 °C	
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL FT1	
Oil resistance:	very good - TM5 acc. to DIN VDE 0281 part 1 + HD 21.1	
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/14	

item no.	dimensions	AWG		largest single wire ø mm	outer-ø approx. mm	copper figure kg/km	cable weight ≈ kg/km
		supply cores	control cores (pairs)				
08631415	4 x 1,50 + (2 x 1,50)	16 / 4c	16 / 1pr	0,26/0,26	10,4	133,4	178
08631425	4 x 2,50 + (2 x 1,50)	14 / 4c	16 / 1pr	0,26/0,26	12,2	196,7	256
08631440	4 x 4,00 + (2 x 1,50)	12 / 4c	16 / 1pr	0,31/0,26	13,7	260,0	324
08631460	4 x 6,00 + (2 x 1,50)	10 / 4c	16 / 1pr	0,31/0,26	16,2	374,9	472
08631470	4 x 10,00 + (2 x 1,50)	8 / 4c	16 / 1pr	0,41/0,26	18,9	542,3	672
08631480	4 x 16,00 + (2 x 1,50)	6 / 4c	16 / 1pr	0,41/0,26	23,3	802,2	975
08631490	4 x 25,00 + (2 x 1,50)	4 / 4c	16 / 1pr	0,41/0,26	26,7	1178,5	1363
08631495	4 x 35,00 + (2 x 1,50)	2 / 4c	16 / 1pr	0,41/0,26	29,8	1586,4	1789

Other dimensions and colours are possible on request.

SIEMENS