



# TRAY CABLES



## TR 600 Auto red

Type TC, MTW and WTTC

UV and oil resistant, flexible Tray Cable and Machine-Tool Cable with red cores for cable tracks



79 600V c(UL) Type CIC 90°C dry 600V FT1 FT2 FT4 CE

Marking for TR 600 Auto red 32111625:

SAB BRÖCKSKES · D-VIERSEN · TR 600 Auto red 16 AWG/25c 32111625 TFFN (UL) Type TC-ER 90°C 600V, Oil Resistant I, Sunlight Resistant, Direct Burial, FT4 (UL) WTTC 90°C 1000V (UL) MTW 16 AWG/25c 600V flexing AWM Style 21179 600V c(UL) Type CIC 90°C dry 600V FT1 FT2 FT4 CE

### Construction:

<b>Conductor:</b>	bare copper strands with reference to IEC 60228 class 6
<b>Insulation:</b>	special formulated PVC/Nylon
<b>Color code:</b>	red cores with numbers; white ground wire and green-yellow earth wire from 3 cores
<b>Stranding:</b>	in layers
<b>Sheath material:</b>	special sunlight and oil resistant PVC
<b>Sheath color:</b>	black (RAL 9005)

### Technical data:

<b>Voltage:</b>	<b>UL-AWM / (UL) / c(UL):</b> 600 V <b>(UL) WTTC:</b> 1000 V
<b>Testing voltage:</b>	4000 V
<b>Min. bending radius</b>	
<i>fixed laying:</i>	< 12 mm = 3 x d > 12 mm = 4 x d
<i>flexible application:</i>	< 12 mm = 5 x d > 12 mm = 6 x d
<i>continuously flexible:</i>	10 x d
<b>Radiation resistance:</b>	8 x 10 <sup>7</sup> cJ/kg
<b>Temperature:</b>	<b>UL-AWM:</b> up to +105°C <b>(UL) / c(UL):</b> -25°C up to +90°C
<i>fixed laying:</i>	
<b>Burning characteristics:</b>	(UL) FT4 + c(UL) FT1, FT2, FT4
<b>Oil resistance I:</b>	yes
<b>Sunlight resistance:</b>	yes
<b>Exposed Runs:</b>	yes
<b>Direct Burial:</b>	yes
<b>Machinery Area:</b>	yes
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

### Outstanding features:

- Flexible cable for cable tray use
- Oil resistance
- Sunlight resistance
- NFPA 79 for industrial machinery
- WTTC approval
- WTTC: UL Subject 2277
- TC: UL Standard 1277
- (UL)/(cUL) listed
- EAC approval

item no.	no. of cores x cross section n x AWG	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
32111803	3 x 18	0,16	7,7	28,8	84
32111804	4 x 18	0,16	8,3	38,4	100
32111805	5 x 18	0,16	9,0	48,0	125
32111807	7 x 18	0,16	10,5	67,2	165
32111809	9 x 18	0,16	11,9	86,4	210
32111812	12 x 18	0,16	12,5	115,2	232
32111816	16 x 18	0,16	14,6	153,6	316
32111818	18 x 18	0,16	15,3	172,8	350
32111819	19 x 18	0,16	16,0	182,4	376
32111825	25 x 18	0,16	18,1	240,0	460
32111603	3 x 16	0,16	8,3	43,2	105
32111604	4 x 16	0,16	9,0	57,6	129
32111605	5 x 16	0,16	9,8	72,0	150
32111607	7 x 16	0,16	11,5	100,8	211
32111608	8 x 16	0,16	12,3	115,2	243

item no.	no. of cores x cross section n x AWG	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
32111609	9 x 16	0,16	13,1	129,6	270
32111612	12 x 16	0,16	14,5	172,8	324
32111616	16 x 16	0,16	16,0	230,4	410
32111618	18 x 16	0,16	16,8	259,2	453
32111619	19 x 16	0,16	17,6	273,6	490
32111625	25 x 16	0,16	19,9	360,0	604
32111403	3 x 14	0,16	9,9	72,0	153
32111404	4 x 14	0,16	10,7	96,0	184
32111405	5 x 14	0,16	11,7	120,0	230
32111407	7 x 14	0,16	14,5	168,0	334
32111409	9 x 14	0,16	16,5	216,0	431
32111412	12 x 14	0,16	17,4	288,0	479
32111418	18 x 14	0,16	20,3	432,0	690
32111425	25 x 14	0,16	25,3	600,0	966
32111007	7 x 10	0,21	18,7	369,6	583

Other dimensions and colours are possible on request.