

CC 540 P PUR-control cable with coloured cores, halogen-free and oil resistant



Marking for CC 540 P 52690415:
SAB BRÖCKSKES · D-VIERSEN · CC 540 P 450/750V 4 G 1,5 mm² CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
Insulation:	SABIX®
Colour code:	coloured acc. to HD 308 (VDE 0293 part 308); green-yellow earth wire from 3 cores
Stranding:	in layers
Sheath material:	PUR, TPU acc. to DIN EN 50363-10-2
Sheath colour:	yellow (RAL 1021)

Outstanding features:

- oil resistant
- abrasion resistant
- notch resistant
- good chemical resistance
- EAC approval

Technical data:

Nominal voltage:	U ₀ /U 300/500 V from 0,75 mm ² to 1,0 mm ² U ₀ /U 450/750 V from 1,0 mm ² to 16,0 mm ²
Testing voltage U:	3000 V acc. to DIN EN 50525-1
Min. bending radius	
<i>fixed laying:</i>	4 x d
<i>flexible application:</i>	6 x d
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range	
<i>fixed laying:</i>	-40/+90 °C
<i>flexible application:</i>	-30/+90 °C
Halogen-free:	acc. to DIN VDE 0472 part 815 + IEC 60754-1
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
Oil resistance:	very good - PUR, TPU acc. to DIN EN 50363-10-2
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Flexibility:	very good
Weather resistance:	good
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/17

300/500 V

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
52690207	2 x 0,75	0,21	6,2	14,4	48
52690307	3 x 0,75	0,21	6,7	21,6	61
52690407	4 x 0,75	0,21	7,3	28,8	75
52690507	5 x 0,75	0,21	8,2	36,0	95
52690211	2 x 1,00	0,21	6,7	19,2	58
52690311	3 x 1,00	0,21	7,1	28,8	71
52690411	4 x 1,00	0,21	7,7	38,4	87
52690511	5 x 1,00	0,21	8,6	48,0	110

450/750 V

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
52690210	2 x 1,00	0,21	7,5	19,2	69
52690310	3 x 1,00	0,21	7,9	28,8	84
52690410	4 x 1,00	0,21	8,8	38,4	106
52690510	5 x 1,00	0,21	9,9	48,0	135
52690215	2 x 1,50	0,26	8,3	28,8	87
52690315	3 x 1,50	0,26	8,8	43,2	106
52690415	4 x 1,50	0,26	9,8	57,6	134
52690515	5 x 1,50	0,26	10,7	72,0	167
52690225	2 x 2,50	0,26	9,8	48,0	127
52690325	3 x 2,50	0,26	10,4	72,0	158
52690425	4 x 2,50	0,26	11,5	96,0	198
52690525	5 x 2,50	0,26	12,9	120,0	252
52690240	2 x 4,00	0,31	11,4	76,8	182
52690340	3 x 4,00	0,31	12,1	115,2	229
52690440	4 x 4,00	0,31	13,4	153,6	289
52690540	5 x 4,00	0,31	15,0	192,0	365
52690260	2 x 6,00	0,31	12,8	115,2	242
52690360	3 x 6,00	0,31	13,8	172,8	312
52690460	4 x 6,00	0,31	15,2	230,4	393
52690560	5 x 6,00	0,31	17,0	288,0	496
52690261	2 x 10,00	0,41	17,1	192,0	428
52690361	3 x 10,00	0,41	18,3	288,0	546
52690461	4 x 10,00	0,41	20,1	384,0	684
52690561	5 x 10,00	0,41	22,3	480,0	856
52690262	2 x 16,00	0,41	19,8	307,2	608
52690362	3 x 16,00	0,41	21,4	460,8	792
52690462	4 x 16,00	0,41	23,3	614,4	988
52690562	5 x 16,00	0,41	26,1	768,0	1248

Other dimensions and colours are possible on request.



Sheath
also possible
in black
or orange