



CC 600 CY Lean PVC control cable with numbered cores and overall copper screen, AWG 8 - AWG 4



21216 90°C Oil 60°C 600V CSA AWM I/II A/B 90° 600V FT1 FT2 CE

Marking for CC 600 CY Lean 32380804:

SAB BRÖCKSKES · D-VIERSEN · CC 600 CY Lean 8 AWG/4c 32380804 AWM Style 21216 90°C Oil 60°C 600V CSA AWM I/II A/B 90° 600V FT1 FT2 CE

Construction:

Conductor:	bare copper strands acc. to UL/CSA
Insulation:	special PVC acc. to DIN VDE and UL/CSA
Colour code:	black cores with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 cores
Stranding:	in layers
Screen:	tinned copper braiding
Sheath material:	special oil resistant PVC acc. to DIN VDE and UL/CSA
Sheath colour:	grey (RAL 7000)

Outstanding features:

- UL recognized, CSA approved
- good EMC characteristics
- reduced outer diameter
- small bending radius
- high mechanical loading capacity
- oil resistant
- EAC approval

Technical data:

Nominal voltage:	DIN VDE U ₀ /U 300/500 V	UL/CSA 600 V
Testing voltage U:	3000 V acc. to DIN VDE 0281 part 2 + HD 21.2; core/screen 1000 V	
Min. bending radius		
<i>fixed laying:</i>	5 x d	
<i>flexible application:</i>	10 x d	
Radiation resistance:	5 x 10 ⁷ cJ/kg	
Temperature range	DIN VDE	UL/CSA:
<i>fixed laying:</i>	-40/+70 °C	up to +90 °C
<i>flexible application:</i>	+5/+70 °C	up to +90 °C
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL VW-1, CSA FT1 + FT2	
Oil resistance:	very good - PVC, TM5 acc. to DIN VDE 0281 part 1 + HD 21.1	
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/17	

item no.	no. of cores x cross section n x AWG	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
32380804	4 x 8	0,41	18,6	508,9	648
32380604	4 x 6	0,41	22,8	753,8	946
32380404	4 x 4	0,41	27,6	1133,3	1462

Other dimensions and colours are possible on request.