

## BiS Besilen® insulating sleeve, non-fibrous



### Outstanding features:

- halogen-free
- flexible at low temperatures
- heat resistant

### Technical data:

<b>Dielectric voltage:</b>	20 kV/mm
<b>Radiation resistance:</b>	$2 \times 10^7$ cJ/kg
<b>Temperature range</b>	
<i>fixed laying:</i>	-40/+180 °C
<i>flexible application:</i>	-25/+180 °C
<i>short-time use:</i>	+250 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 and IEC 60754-1
<b>Corrosiveness of conflagration gases:</b>	IEC 60754-2 + EN 50267-2-2 + VDE 0482 part 267-2-2 – no development of corrosive conflagration gases
<b>Chem. resistance:</b>	see page N/9
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/14

item no.	inside diameter x wall thickness mm	outer ø mm	weight approx. ≈ kg/km
01001004	1,0 x 0,40	1,8	2,2
01001504	1,5 x 0,40	2,3	3,0
01001506	1,5 x 0,60	2,7	5,7
01002004	2,0 x 0,40	2,8	3,8
01002504	2,5 x 0,40	3,3	4,7
01003004	3,0 x 0,40	3,8	5,5
01004005	4,0 x 0,50	5,0	8,9
01004007	4,0 x 0,75	5,5	14,2
01006009	6,0 x 0,90	7,8	23,5
01007009	7,0 x 0,90	8,8	27,0
01008010	8,0 x 1,00	10,0	34,0
01005210	10,0 x 1,00	12,0	44,0