

COMPENSATING AND EXTENSION CABLES

also available
as halogen-free
construction!

PVC insulated cables A 9 L · A 9-100 L · A 9-075 L · A 9-050 L · A 9-022 L



A 9 L · A 9-100 L · A 9-075 L · A 9-050 L

A 9-022 L

Construction:

Insulation:	PVC acc. to T12 acc. to DIN VDE 0281 part 1 + HD 21.1
Stranding:	2 cores together
Sheath:	PVC TM2 acc. to DIN VDE 0281 part 1 + HD 21.1
Shape:	round
Conductor construction:	strand

Technical data:

Min. bending radius:	7,5 x d
Radiation resistance:	8 x 10 ⁻⁷ cJ/kg
Temperature range of insulation:	fixed laying: -40/+70 °C flexible application: +5/+70 °C
Insulation resistance:	> 1MΩ x km
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/14

A 9-022 L:
New Item!
Old Item 0450

Type:	A 9 L	A 9-100 L	A 9-075 L	A 9-050 L	A 9-022 L
Conductor cross section:	1,5 mm ²	1,0 mm ²	0,75 mm ²	0,50 mm ²	0,22 mm ²
Outer diameter:	approx. 6,1 mm	approx. 5,1 mm	approx. 4,9 mm	approx. 4,3 mm	approx. 3,3 mm
Weight/100m:	approx. 5,0 kg	approx. 4,4 kg	approx. 3,9 kg	approx. 2,9 kg	approx. 1,6 kg

DIN IEC 584

for thermocouple	EMK at 100 °C in mV	cable type	A 9 L item no.	A 9-100 L item no.	A 9-075 L item no.	A 9-050 L item no.	A 9-022 L item no.
Type T	4,28	TX	04428958	04426958	04425958	04423958	04421958
Type J	5,27	JX	04428952	04426952	04425952	04423952	04421952
Type K	4,10	KCA	04428995	04426995	04425995	04423995	04421995
Type K	4,10	KCB	04428999	04426999	04425999	04423999	04421999
Type K	4,10	KX	04428954	04426954	04425954	04423954	04421954
Type E	6,32	EX	04428953	04426953	04425953	04423953	04421953
Type R/S	0,65	R/SCB	04428997	04426997	04425997	04423997	04421997
Type N	2,77	NC	04428991	04426991	04425991	04423991	04421991

We also manufacture compensating and extension cables colour coded to DIN VDE 43714 – 06/79 and the basic values laid down in DIN VDE 43710 which was withdrawn in April 1994.

DIN 43710 / 43714 (not valid for *type B)

for thermocouple	EMK at 100 °C in mV	cable type	A 9 L item no.	A 9-100 L item no.	A 9-075 L item no.	A 9-050 L item no.	A 9-022 L item no.
Type L	5,37	LX	04428992	04426992	04425992	04423992	04421992
Type K	4,10	KCA	04428994	04426994	04425994	04423994	04421994
Type R/S	0,65	R/SCB	04428996	04426996	04425996	04423996	04421996
Type U	4,25	UX	04428993	04426993	04425993	04423993	04421993
*Type B	0,00	BC-100	04428901	04426901	04425901	04423901	04421901
*Type B	0,033	BC-200	04428902	04426902	04425902	04423902	04421902

*Not standardized compensating cable for thermocouples type B with application temperatures up to 100°C resp. 200 °C.

C = compensating cables · X = extension cables