

Also available in
type K, T or L* and
classes 1 or 2!

For the temperature collection at plastics processing machines or similar. The stainless steel wire armouring of the connection cable is used as mechanical protection.



THERMOCOUPLE - CLASS 2:

- 1 x type J 1 x type K other thermocouples: _____

MEASURING POINT:

- form A, insulated form B, grounded

MATERIAL:

- 1.4541

NOMINAL LENGTH: _____ mm

DIAMETER:

- Ø 3,0 mm Ø 4,0 mm Ø 6,0 mm
 Ø 3,5 mm Ø 5,0 mm Ø 8,0 mm

BOTTOM SHAPE:

- flat 118°C spherical

OPTIONAL WITH SHEET:

- 8 x 15 mm / hole Ø 5 mm dimension: _____

TYPE:

- with kink protection with fiberglass sleeve

CONNECTION CABLE:

(see also survey of connecting cables for thermocouples)

- extension cable strand/fiber glass/fiber glass/
stainless steel wire armouring +400°C
 extension cable strand/PFA/fiber glass/
stainless steel wire armouring +250°C
 extension cable strand/PFA/PFA +250°C

CABLE LENGTH: _____ m

CONNECTION ENDS:

- miniature thermoplug miniature socket
 standard plug Lemo plug type _____
 clips Lemo socket type _____
 bare ends other cable ends _____



- The above mentioned technical data are standard data.
- Individual parameters, e. g. connection cable, double thermocouple or cable end can be added or modified on request.