

# Cable Track Cable

## SD 960 CP

continuously flexible PUR data cable with coloured cores and overall copper screen



Marking for SD 960 CP 07862501:

SAB BRÜCKSKES · D-VIERSEN · 07862501 25 x 0,14 mm<sup>2</sup> SD 960 CP 26 AWG/25c 07862625

UL AWM Style 20233 80°C 300V CSA AWM I/II A/B 80°C 300V FT1 FT2 CE

### Construction:

<b>Conductor:</b>	bare copper strands, extra fine wires
<b>Insulation:</b>	PVC, TI2 acc. to EN 50363-3 + VDE 0207-363-3
<b>Colour code:</b>	with reference to colour code US 2, see chapter N „Technical Data“
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Wrapping:</b>	non-woven tape
<b>Screen:</b>	tinned copper braiding
<b>Wrapping:</b>	non-woven tape
<b>Sheath material:</b>	PU acc. to UL 758 with mat surface
<b>Sheath colour:</b>	grey (RAL 7032)

### Technical Data:

<b>Peak operating voltage:</b>	max. 350 V	
<b>Voltage UL/CSA:</b>	300 V	
<b>Testing voltage:</b>	core/core	1500 V
	core/screen	1200 V
<b>Min. bending radius</b> <i>continuously flexible:</i>	7,5 x d	
<b>Radiation resistance:</b>	5 x 10 <sup>7</sup> cJ/kg	
<b>Temperature range</b>	<b>DIN VDE</b>	<b>UL/CSA:</b> up to +80 °C
<i>fixed laying:</i>	-30/+70 °C	
<i>flexible application:</i>	-5/+70 °C	
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to UL FT1, CSA FT1, FT2	
<b>Oil resistance:</b>	very good - oilrating 60 °C acc. to UL 758	
<b>Chem. resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.	
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union, see chapter N „Technical Data“	

### Outstanding features:



- very good EMC characteristics
- high abrasion resistance
- very good flexibility

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
07860201	2 x 0,14	0,11	5,0	16,5	31
07860301	3 x 0,14	0,11	5,2	17,9	33
07860401	4 x 0,14	0,11	5,6	19,4	38
07860501	5 x 0,14	0,11	6,0	22,7	45
07860701	7 x 0,14	0,11	6,8	27,1	56
07861001	10 x 0,14	0,11	7,7	34,9	68
07861401	14 x 0,14	0,11	8,9	41,9	88
07861801	18 x 0,14	0,11	9,1	50,5	102
07862501	25 x 0,14	0,11	11,2	81,5	147
07860202	2 x 0,25	0,11	5,3	18,7	33
07860302	3 x 0,25	0,11	5,6	21,2	39
07860402	4 x 0,25	0,11	5,9	25,5	45
07860502	5 x 0,25	0,11	6,4	28,1	53
07860702	7 x 0,25	0,11	8,1	36,5	81

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
07861002	10 x 0,25	0,11	9,0	49,8	89
07861402	14 x 0,25	0,11	9,6	61,9	111
07861802	18 x 0,25	0,11	9,8	72,4	129
07862502	25 x 0,25	0,11	12,1	114,5	187
07860203	2 x 0,34	0,11	5,5	20,5	36
07860303	3 x 0,34	0,11	5,8	23,9	42
07860403	4 x 0,34	0,11	6,2	29,1	50
07860503	5 x 0,34	0,11	6,6	34,0	59
07860703	7 x 0,34	0,11	7,6	44,2	73
07861003	10 x 0,34	0,11	9,4	70,8	122
07861403	14 x 0,34	0,11	10,0	86,8	154
07861803	18 x 0,34	0,11	10,5	106,4	161
07862503	25 x 0,34	0,11	12,7	141,2	215

Other dimensions and colours are possible on request.

### Possible on request:

- in dimensions  
0,50 mm<sup>2</sup> and 0,75 mm<sup>2</sup>
- with orange outer sheath  
and coloured cores  
with reference to DIN 47100

