

USB 2.0 Cables continuously flexible



Marking for USB 2.0 06010122:

SAB BRÖCKSKES · D-VIERSEN · USB 2.0 (2x0,22mm²) ST + 2x0,5mm² 0601-0122 CE



Construction:	USB 2.0 S <i>suitable for cable tracks</i>	USB 2.0 S UL/CSA <i>suitable for cable tracks</i>	USB 2.0 RT UL/CSA <i>suitable for robots</i>
Dimension:	(2 x 0,22 mm ²) ST + 2 x 0,5 mm ²		
Conductor:	bare copper strands (0,50 mm ²), silver-plated strands (0,22 mm ²)		
Insulation:	SABIX®		
Colour code:	black, red (0,50 mm ²), white, green (0,22 mm ²)		
Stranding:	2 x 0,22 mm ² wrapped with alu foil, together with 0,5 mm ²		
Wrapping:	non-woven tape	PTFE foil	
Screen:	tinned copper braiding	wrapping with tinned copper round wires	
Wrapping:	non-woven tape		
Sheath material:	PUR		
Sheath colour:	black (RAL 9005)		

Technical data:	USB 2.0 S <i>suitable for cable tracks</i>	USB 2.0 S UL/CSA <i>suitable for cable tracks</i>	USB 2.0 RT UL/CSA <i>suitable for robots</i>
Item number:	0601-1022	0601-1122	0601-2022
Peak operating voltage VDE:	max. 350 V		
Voltage UL/CSA:	---	300 V	
Testing voltage:	core/core 2000 V - core/screen 2000 V		
Temperature range VDE	UL/CSA: up to + 80°C		
fixed laying:	- 50°C / + 90 °C	- 50°C / + 90 °C	
flexible application:	- 40°C / + 90 °C	- 40°C / + 90 °C	
Min. bending radius			
fixed laying:	5 x d		5 x d
flexible application:	6 x d		7,5 x d
continuously flexible:	7,5 x d		10 x d
torsion angle:			up to +/- 180°/m
Halogen-free:	acc. to DIN VDE 0472 part 815 + IEC 60754-1		---
Oil resistance:	TMPU acc. to DIN VDE 0282 part 10 + HD 22.10		
Absence of harmful substances:	acc. to RoHS directive of the European Union, see page N/17		

item no.	type	dimension mm ²	outer-ø approx. mm	copper figure kg/km	cable weight ≈kg/km
06011022	USB 2.0 S	(2x0,22) ST + 2x0,50	7,0	34,1	59
06011122	USB 2.0 S UL/CSA	(2x0,22) ST + 2x0,50	7,2	34,1	66
06012022	USB 2.0 RT UL/CSA	(2x0,22) ST + 2x0,50	7,0	34,3	64

Other dimensions and colours are possible on request.