

## RG 179 FEP FEP insulated coaxial cable with FEP jacket in reference to RG 179 (75 Ω)



### Construction:

Conductor:	silver-plated strands, fine wires (7 wires)
Insulation:	FEP
Color code:	nature
Screen:	silver-plated braiding
Sheath material:	FEP
Sheath color:	black (RAL 9005)

### Outstanding features:

- excellent resistance against chemicals and solvents
- excellent temperature resistance and flexibility at low temperatures
- excellent electrical insulating characteristics with low, nearly frequency-independent dielectric characteristics
- EAC approval

### Technical data:

Frequency range:	max. 1 GHz
Peak operating voltage:	900 V
Testing voltage:	2000 V
Min. bending radius:	7.5 x d
Intrinsic impedance:	75 Ω ± 5 Ω
Spreading velocity:	approx. 69%
Capacitance:	max. 75 pF/m
Conductor resistance:	max. 363 Ω/km
Attenuation at 20 °C:	50 MHz approx. 15 dB/100 m 100 MHz approx. 20 dB/100 m 400 MHz approx. 55 dB/100 m 900 MHz approx. 70 dB/100 m 1000 MHz approx. 85 dB/100 m 1800 MHz approx. 90 dB/100 m 3000 MHz approx. 110 dB/100 m
Regularity:	50 MHz up to 400 MHz > 26 dB 400 MHz up to 1000 MHz > 24 dB 1000 MHz up to 3000 MHz > 20 dB
Temperature range	
fixed laying:	-90/+180 °C
flexible application:	-55/+180 °C
Chem. resistance:	very good against acids, halogens, bases, chlorinated solvents as well as organic and inorganic compounds
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/17

item no.	nominal cross-section mm <sup>2</sup>	nominal single wire ø mm	outer-ø mm	copper figure kg/km	cable weight ≈ kg/km
36200062	1 x 0,055	0,11	2,54 ± 0,12 mm	9,5	16

Other dimensions and colours are possible on request.