

Besilen® - Silicone Cables

B 118

Besilen® insulated strands Uo/U 0.6/1 kV

On request with
 recognition

Nominal voltage
 Uo/U 0.6/1 kV



Application: These insulated strands with 0,6/1 kV are for example used in switchboards and distributors, in industrial furnaces and textile machine construction as well as in railway technology. Equally they are applied as connection of battery system or energy storage.

Construction:

Conductor: tinned copper strands,
 acc. to IEC 60228, VDE 0295, class 5

Insulation: Besilen® EI2
 acc. to EN 50363-1 + VDE 0207-363-1

Outstanding features:

- » halogen-free
- » flexible at low temperatures
- » heat resistant

Technical data:

Nominal voltage: Uo/U 0,6/1 kV

Testing voltage: 2500 V

Current-carrying capacity: acc. to VDE 0298-4, see chapter N „Technical data“

Min. bending radius: 7.5 x d

Temperature range
fixed laying: -40/+180 °C
flexible application: -25/+180 °C

Halogen-free: acc. to IEC 60754-1 + VDE 0482-754-1

Fire performance: flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2

Corrosiveness of conflagration gases: IEC 60754-2 + VDE 0482-754-2
 - no development of corrosive conflagration gases

Weather resistance: very good

Absence of harmful substances: acc. to RoHS directive of the European Union, see chapter N „Technical data“

item no.	nominal cross section mm ²	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
0118 .. 50*	0,50	0,21	2,5	4,8	10
0118 .. 75*	0,75	0,21	2,8	7,2	13
0118 .. 80*	1,00	0,21	2,9	9,6	16
0118 .. 82*	1,50	0,26	3,2	14,4	20
0118 .. 84*	2,50	0,26	3,8	24,0	31
0118 .. 86*	4,00	0,31	4,6	38,4	48
0118 .. 87*	6,00	0,31	5,1	57,6	66
0118 .. 88*	10,00	0,41	6,7	96,0	113
0118 .. 89*	16,00	0,41	8,1	153,6	171
0118 .. 90*	25,00	0,41	9,9	240,0	262
0118 .. 91*	35,00	0,41	11,3	336,0	361
0118 .. 92*	50,00	0,41	12,9	480,0	527
0118 .. 93*	70,00	0,41	15,2	672,0	696
0118 .. 94*	95,00	0,51	17,7	912,0	948
0118 .. 95*	120,00	0,51	19,6	1152,0	1161
0118 .. 96*	150,00	0,51	21,5	1440,0	1452
0118 .. 97*	185,00	0,51	23,6	1776,0	1776
0118 .. 98*	240,00	0,51	27,3	2304,0	2378
0118 .. 99*	300,00	0,51	30,4	2880,0	2963

Other dimensions and colours are possible on request.

* Colour code for single conductors, position 5 and 6 of the item no.:

- | | |
|-------------|-------------------|
| 01 = black | 06 = green |
| 02 = blue | 07 = violet |
| 03 = brown | 08 = white |
| 04 = grey | 16 = gentian blue |
| 05 = yellow | 27 = green-yellow |

