

## BiHF(K)-J Besilen® insulated strands with extremely notch resistant Besilen® outer sheath



### Construction:

<b>Conductor:</b>	tinned copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
<b>Insulation:</b>	Besilen® EI2 acc. to DIN EN 50363-1
<b>Colour code:</b>	up to 5 cores coloured acc. to HD 308 (VDE 0293 part 308); from 6 cores black cores with consecutive numbers acc. to EN 50334; from 3 cores a green-yellow earth wire
<b>Stranding:</b>	in layers
<b>Sheath material:</b>	Besilen® notch resistant
<b>Sheath colour:</b>	black (similar RAL 9011)

### Outstanding features:

- improved initial tear resistance
- improved tear-growth resistance
- extremely notch resistant
- good sunlight resistance
- halogen-free
- flexible at low temperatures
- heat resistant
- EAC approval

### Technical data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 300/500 V
<b>Testing voltage:</b>	2000 V
<b>Min. bending radius</b>	
<i>fixed laying:</i>	4 x d
<i>flexible application:</i>	6 x d
<b>Radiation resistance:</b>	2 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b>	
<i>fixed laying:</i>	-40/+180 °C
<i>flexible application:</i>	-25/+180 °C
<i>short-time use:</i>	+250 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 + IEC 60754-1
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
<b>Corrosiveness of conflagration gases:</b>	IEC 60754-2 + EN 50267-2-2 + VDE 0482 part 267-2-2 - no development of corrosive conflagration gases
<b>Chem. resistance:</b>	see page N/11
<b>Weather resistance:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
01450207	2 x 0,75	0,21	5,4	14,4	40
01450307	3 x 0,75	0,21	5,7	21,6	49
01450407	4 x 0,75	0,21	6,2	28,8	59
01450507	5 x 0,75	0,21	6,9	36,0	71
01450707	7 x 0,75	0,21	7,7	50,4	96
01451207	12 x 0,75	0,21	10,3	86,4	157
01450210	2 x 1,00	0,21	5,6	19,2	45
01450310	3 x 1,00	0,21	5,9	28,8	56
01450410	4 x 1,00	0,21	6,5	38,4	69
01450510	5 x 1,00	0,21	7,1	48,0	83
01450710	7 x 1,00	0,21	8,0	67,2	112
01451210	12 x 1,00	0,21	10,7	115,2	185
01450215	2 x 1,50	0,26	6,6	28,8	64
01450315	3 x 1,50	0,26	7,0	43,2	79
01450415	4 x 1,50	0,26	7,8	57,6	101
01450515	5 x 1,50	0,26	8,6	72,0	121
01450715	7 x 1,50	0,26	9,4	100,8	158

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
01451215	12 x 1,50	0,26	12,8	172,8	265
01451815	18 x 1,50	0,26	15,4	259,2	391
01452415	24 x 1,50	0,26	18,2	345,6	521
01452515	25 x 1,50	0,26	18,6	360,0	540
01450225	2 x 2,50	0,26	8,0	48,0	97
01450325	3 x 2,50	0,26	8,5	72,0	122
01450425	4 x 2,50	0,26	9,3	96,0	151
01450525	5 x 2,50	0,26	10,6	120,0	191
01450625	6 x 2,50	0,26	11,6	144,0	223
01450725	7 x 2,50	0,26	11,6	168,0	250
01450340	3 x 4,00	0,31	10,2	115,2	184
01450440	4 x 4,00	0,31	11,1	153,6	228
01450540	5 x 4,00	0,31	12,5	192,0	280
01450740	7 x 4,00	0,31	13,6	268,8	369
01450360	3 x 6,00	0,31	11,4	172,8	251
01450460	4 x 6,00	0,31	12,5	230,4	315
01450560	5 x 6,00	0,31	13,8	288,0	381

Other dimensions and colours are possible on request.