



## SC 600 C HDTR SABIX® insulated strands with overall copper screen and Besilen® outer sheath

Style 4535 150°C 600V CSA AWM I/II A 150°C 600V FT1 FT2 CE



Marking for SC 600 C HDTR 01240410:

SAB BRÖCKSKES · D-VIERSEN · SC 600 C HDTR AWM Style 4535 150°C 600V CSA AWM I/II A 150°C 600V FT1 FT2 CE

### Construction:

<b>Conductor:</b>	tinned copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 5
<b>Insulation:</b>	SABIX®
<b>Colour code:</b>	up to 5 cores coloured acc. to HD 308 (VDE 0293 part 308); from 6 cores black cores with consecutive numbers acc. to EN 50334; from 3 cores a green-yellow earth wire
<b>Stranding:</b>	in layers
<b>Inner sheath:</b>	Besilen® EM9 acc. to DIN EN 50363-2-1
<b>Screen:</b>	tinned copper braiding
<b>Sheath material:</b>	Besilen® better than EM9 acc. to DIN EN 50363-2-1
<b>Sheath colour:</b>	black (similar RAL 9011)

### Technical data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 300/500 V
<b>Voltage UL/CSA:</b>	600 V
<b>Testing voltage:</b>	2000 V acc. to DIN VDE 0282 part 2 + HD 22.2
<b>Min. bending radius</b>	
<i>fixed laying:</i>	4 x d
<i>flexible application:</i>	6 x d
<b>Radiation resistance:</b>	2 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b>	
<i>fixed laying:</i>	<b>UL/CSA:</b> up to +150 °C Style 4535
<i>flexible application:</i>	<b>DIN VDE:</b> -40/+180 °C / +200 °C (2000 h)
<i>short-time use:</i>	-25/+180 °C +250 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 + IEC 60754-1
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, CSA FT1 + FT2
<b>Corrosiveness of conflagration gases:</b>	IEC 60754-2 + EN 50267-2-2 + VDE 0482 part 267-2-2 - no development of corrosive conflagration gases
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

### Outstanding features:

- good EMC characteristics
- halogen-free
- flexible at low temperatures
- heat resistant
- UL recognized, CSA approved
- EAC approval

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
01240207	2 x 0,75	0,21	8,2	37,0	93
01240307	3 x 0,75	0,21	8,5	44,4	101
01240407	4 x 0,75	0,21	9,0	55,0	123
01240507	5 x 0,75	0,21	9,7	62,9	139
01240210	2 x 1,00	0,21	8,4	42,0	101
01240310	3 x 1,00	0,21	8,7	54,7	120
01240410	4 x 1,00	0,21	9,3	64,8	136
01240510	5 x 1,00	0,21	10,1	93,8	167
01240710	7 x 1,00	0,21	11,0	114,3	202
01240215	2 x 1,50	0,26	9,4	55,3	129
01240315	3 x 1,50	0,26	10,0	88,8	164
01240415	4 x 1,50	0,26	10,8	104,4	192

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
01240515	5 x 1,50	0,26	11,6	125,5	235
01240715	7 x 1,50	0,26	12,8	161,0	277
01240225	2 x 2,50	0,26	11,2	99,8	210
01240325	3 x 2,50	0,26	11,7	124,5	233
01240425	4 x 2,50	0,26	12,9	156,3	282
01240525	5 x 2,50	0,26	14,3	187,0	336
01240340	3 x 4,00	0,31	13,8	177,1	329
01240440	4 x 4,00	0,31	14,8	221,5	384
01240540	5 x 4,00	0,31	16,7	292,3	481
01240360	3 x 6,00	0,31	15,1	241,2	396
01240460	4 x 6,00	0,31	16,8	330,9	524
01240560	5 x 6,00	0,31	18,1	400,8	581

Other dimensions and colours are possible on request.

K  
30



Temperature range  
up to +200°C Style 4511  
with nickel or silver  
plated copper strands.  
Please contact SAB!