

Industrial Ethernet cables

CATLine CAT 5e DR reeling CAT 5e
Industrial Ethernet cable
CATLine CAT 6A DR reeling CAT 6A
Gigabit Ethernet cable

CATLine CAT 7A DR
reeling CAT 7A Gigabit Ethernet cable



SEN · CATLine Cat. 7A DR 4x2x26AWG 1739-4651 CE



marking example:

SAB BRÜCKSKES · D-VIERSEN · CATLine Cat. 7A DR 4x2x26AWG 1739-4651 CE

Construction:	CATLine CAT 5e DR reeling Ethernet cable	CATLine CAT 6A DR reeling Ethernet cable	CATLine CAT 7A DR reeling Ethernet cable
Dimension:	4 x 2 x 26 AWG		
Conductor:	bare copper strands, fine wires		
Insulation:	special polymer		
Colour code:	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown		
Stranding:	cores twisted to pairs, pairs together		cores twisted to pairs, pairs screened with foil, pairs together
Wrapping:	non-woven tape		—
Screen:	alu foil and tinned copper braiding		aluminized non-woven tape and tinned copper braiding
Wrapping:	non-woven tape		
Sheath material:	PUR / supporting braid / PUR		
Sheath colour:	black (RAL 9005)		

Technical data:	CATLine CAT 5e DR reeling Ethernet cable	CATLine CAT 6A DR reeling Ethernet cable	CATLine CAT 7A DR reeling Ethernet cable
Item number:	1539-4651	1639-4651	1739-4651
Peak operating voltage:	max. 90 V		
Testing voltage	750 V		
core/core:	750 V		
core/screen:	750 V		
Min. bending radius:	for laying and installation (fixed laying): 5 x d for repeated winding action (flexible application): 10 x d guided on pulleys (flexible application): 12 x d		
Temperature range	-50/+90 °C		
fixed laying:	-40/+90 °C		
flexible application:	acc. to IEC 60754-1 + VDE 0482-754-1		
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1		
Oil resistance:	TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2		
Characteristic impedance:	100Ω ± 10Ω, fulfils the electrical and transmission requirements with high frequency with reference to EN 50288-2-2 / CAT 5	100Ω ± 10Ω, fulfils the electrical and transmission requirements with high frequency with reference to EN 50288-10-2 / CAT 6A	100Ω ± 10Ω, fulfils the electrical and transmission requirements with high frequency with reference to EN 50288-9-2 / CAT 7A
Weather resistance:	very good		
Application:	suitable for EtherCAT and EtherNET/IP applications		
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“		

item no.	type	dimension	max. core-ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km	tensile strength max. N
15394651	CATLine CAT 5e DR	4 x 2 x 26 AWG	1,05	8,5	32,0	79	200
16394651	CATLine CAT 6A DR	4 x 2 x 26 AWG	1,05	8,5	32,0	81	200
17394651	CATLine CAT 7A DR	4 x 2 x 26 AWG	1,05	10,5	38,5	117	200

Other dimensions and colours are possible on request.

Also possible
as harnessed cable
with M12 or RJ 45 plug!

