

# Tray Cables

## TR 600 Auto blue Type TC, MTW and WTTC

UV and oil resistant, flexible Tray Cable and Machine-Tool Cable with blue cores for cable tracks

WTTC approval

NFPA 79 for industrial machinery

high-flex

179 600V c(UL) Type CIC 90°C dry 600V FT1 FT2 FT4 CE



Marking example:

SAB BRÖCKSKES · D-VIERSEN · TR 600 Auto blue 16 AWG/12c 32101612 TFFN (UL) Type TC-ER 90°C 600V, Oil Resistant I, Sunlight Resistant, Direct Burial, FT4 (UL) WTTC 90°C 1000V (UL) MTW 16 AWG/12c 600V flexing AWM Style 21179 600V c(UL) Type CIC 90°C dry 600V FT1 FT2 FT4 CE

### Construction:

<b>Conductor:</b>	bare copper strands with reference to IEC 60228, VDE 0295 class 6
<b>Insulation:</b>	special formulated PVC/Nylon
<b>Colour code:</b>	blue cores with numbers, white-blue ground wire and green-yellow earth wire from 3 cores
<b>Stranding:</b>	in layers
<b>Sheath material:</b>	special sunlight and oil resistant PVC
<b>Sheath colour:</b>	black (RAL 9005)

### Outstanding features:

- » Flexible cable for cable tray use
- » Oil resistance
- » Sunlight resistance
- » NFPA 79 for industrial machinery
- » WTTC approval
- » WTTC: UL Subject 2277
- » TC: UL Standard 1277
- » UL recognized, (UL)/c(UL) listed
- » PFAS free

### Technical data:

<b>Voltage</b>	600 V
<b>UL-AWM / (UL) / c(UL):</b>	1000 V
<b>(UL) WTTC:</b>	
<b>Testing voltage:</b>	AWG 18-10 = 6000 V AWG 8-2 = 7500 V
<b>Min. bending radius:</b>	
<i>fixed laying:</i>	< 12 mm = 3 x d > 12 mm = 4 x d
<i>flexible application:</i>	< 12 mm = 5 x d > 12 mm = 6 x d
<i>continuously flexible:</i>	10 x d
<b>Radiation resistance:</b>	8 x 10 <sup>7</sup> cJ/kg
<b>Temperature:</b>	UL-AWM: up to +105 °C (UL) / c(UL): up to +90 °C -25 °C
<i>fixed laying:</i>	
<b>Burning characteristics:</b>	(UL) FT4 + c(UL) FT1, FT2, FT4
<b>Oil resistance I:</b>	yes
<b>Sunlight resistance:</b>	yes
<b>Exposed Runs:</b>	yes
<b>Direct Burial:</b>	yes
<b>Machinery Area:</b>	yes
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union, see chapter N „Technical data“

item no.	no. of cores x cross section n x AWG	largest single wire Ø mm	outer-Ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
32101803	3 x 18	0,16	7,7	28,8	84
32101804	4 x 18	0,16	8,3	38,4	100
32101805	5 x 18	0,16	9,0	48,0	125
32101807	7 x 18	0,16	10,5	67,2	165
32101809	9 x 18	0,16	11,9	86,4	210
32101812	12 x 18	0,16	12,5	115,2	232
32101816	16 x 18	0,16	14,6	153,6	316
32101818	18 x 18	0,16	15,3	172,8	350
32101819	19 x 18	0,16	16,0	182,4	376
32101825	25 x 18	0,16	18,1	240,0	460
32101603	3 x 16	0,16	8,3	43,2	105
32101604	4 x 16	0,16	9,0	57,6	129
32101605	5 x 16	0,16	9,8	72,0	150
32101607	7 x 16	0,16	11,5	100,8	211
32101608	8 x 16	0,16	12,3	115,2	243

item no.	no. of cores x cross section n x AWG	largest single wire Ø mm	outer-Ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
32101609	9 x 16	0,16	13,1	129,6	270
32101612	12 x 16	0,16	14,5	172,8	324
32101616	16 x 16	0,16	16,0	230,4	410
32101618	18 x 16	0,16	16,8	259,2	453
32101619	19 x 16	0,16	17,6	273,6	490
32101625	25 x 16	0,16	19,9	360,0	604
32101403	3 x 14	0,16	9,9	72,0	153
32101404	4 x 14	0,16	10,7	96,0	184
32101405	5 x 14	0,16	11,7	120,0	230
32101407	7 x 14	0,16	14,5	168,0	334
32101409	9 x 14	0,16	16,5	216,0	431
32101412	12 x 14	0,16	17,4	288,0	479
32101418	18 x 14	0,16	20,3	432,0	690
32101425	25 x 14	0,16	25,3	600,0	966
32101007	7 x 10	0,21	18,7	369,6	583

Other dimensions and colours are possible on request.